

CONCRETE BATCHING PLANTS & MIXERS



ISO 9001:2015 CERTIFIED

LAL'S
ASPHALT & CONCRETE EQUIPMENT



TECHNICAL SPECIFICATION

DESCRIPTION / Model	LSCP 30	LSCP 45	LSCP 60	LSCP 75	LSCP 90	LSCP 120
Mixer Type	Pan / Twin Shaft	Pan / Twin Shaft	Twin Shaft	Twin Shaft	Twin Shaft	Twin Shaft
Batch Capacity	0.50 Cum	0.75 Cum	1.0 Cum	1.25 Cum	1.5 Cum	2.0 Cum
Output Capacity	30 Cum / Hr.	45 Cum / Hr.	60 Cum / Hr.	75 Cum / Hr.	90 Cum / Hr.	120 Cum / Hr.
Main Mixer Drive	25 HP	40 HP / 30 HP	50 HP	60 HP	100 HP	150 HP
No. of Bins (Inline)	4 Bins (In-Line Bin : 03 Agg + 01 Sand)					
Storage capacity	32 Cum	48 Cum	60 Cum	80 Cum	100 Cum	133 Cum
Material Weighing	Digital Load Cell based weighing system separately for aggregate, cement, water and additive					
Batch Feeding	Through Inclined Conveyor Belt					
Control Panel	PLC Based Fully Automatic Control Panel with DELTA HMI DISPLAYS					
Control Cabin	Size of 6' x 6' - Insulated, lockable door, fitted with lights					
Suggested DG Set	82 KVA	125 KVA	160 KVA	200 KVA	300 KVA	400 KVA



COMPACT CONCRETE BATCHING PLANT

LAL'S
ASPHALT & CONCRETE EQUIPMENT



TECHNICAL SPECIFICATION

DESCRIPTION / Model	LCP 20	LCP 24	LCP 30	LCP 45	LCP 60
Mixer Type	Pan	Pan	Pan / Twin Shaft	Pan / Twin Shaft	Pan / Twin Shaft
Batch Capacity	0.33 Cum	0.40 Cum	0.50 Cum	0.75 Cum	1.0 Cum
Output Capacity	20 Cum / Hr.	24 Cum / Hr.	30 Cum / Hr.	45 Cum / Hr..	60 Cum / Hr..
Main Mixer Drive	20 HP	20 HP	25 HP	40 HP / 30 HP	50 HP
No. of Bins (Inline)	4 Bins (2 X 2 Cross Bins : 03 Agg + 01 Sand)				
Storage capacity	14 Cum	16 Cum	26 Cum	30 Cum	40 Cum
Material Weighing	Digital Load Cell based weighing system separately for aggregate, cement, water and additive				
Batch Feeding	Through Inclined Conveyor Belt				
Control Panel	PLC Based Fully Automatic Control Panel with DELTA HMI DISPLAYS				
Control Cabin	Size of 6' x 6' - Insulated, lockable door, fitted with lights				
Suggested DG Set	62 KVA	62 KVA	82 KVA	100 KVA	125 KVA



PORTABLE CONCRETE BATCHING PLANT

LAL'S
ASPHALT & CONCRETE EQUIPMENT



TECHNICAL SPECIFICATION

DESCRIPTION / Model	LPCP 15	LPCP 24	LPCP 30
Mixer Type	Pan	Pan	Pan
Batch Capacity	0.25 Cum	0.40 Cum	0.50 Cum
Output Capacity	15 Cum / Hr.	24 Cum / Hr.	30 Cum / Hr.
Main Mixer Drive	15 HP	20 HP	25 HP
No. of Bins (Inline)	4 Bins (2 X 2 Cross Bins : 03 Agg + 01 Sand)		
Storage capacity	12 Cum	12 Cum	12 Cum
Material Weighing	Digital Load Cell based weighing system separately for aggregate, cement, water and additive		
Batch Feeding	Through Inclined Conveyor Belt		
Control Panel	PLC Based Fully Automatic Control Panel with DELTA HMI DISPLAYS		
Control Cabin	Size of 6' x 6' - Insulated, lockable door, fitted with lights		
Suggested DG Set	61 KVA	62 KVA	82 KVA



CONCRETE BATCHING PLANT WITH REVERSIBLE MIXER

LAL'S
ASPHALT & CONCRETE EQUIPMENT



TECHNICAL SPECIFICATION

DESCRIPTION / Model	LRMB 15	LRMB 20	LRMB 30
Mixer Type	Reversible Drum Mixer	Reversible Drum Mixer	Reversible Drum Mixer
Batch Capacity	0.40 Cum	0.50 Cum	0.75 Cum
Output Capacity	15 Cum / Hr.	20 Cum / Hr.	30 Cum / Hr.
Main Mixer Drive	10 HP	12.5 HP	15 HP
No. of Bins (Inline)	4 Bins (2 X 2 Cross Bins : 03 Agg + 01 Sand)		
Storage capacity	9 Cum	9 Cum	12 Cum
Material Weighing	Digital Load Cell based separate weighing for aggregate, cement, water and additive		
Batch Feeding System	Through Inclined Conveyor Belt		
Control Panel	PLC Based Fully Automatic Control Panel with DELTA HMI DISPLAYS		
Control Cabin	Size of 6' x 6' - Insulated, lockable door, fitted with lights		
Suggested DG Set	40 KVA	50 KVA	62 KVA





TECHNICAL SPECIFICATION

DESCRIPTION / Model	LRM 10 (ELECTRIC)	LRM 12 (ELECTRIC)	LRM 15 (ELECTRIC)
Mixer Type	Reversible Drum Mixer	Reversible Drum Mixer	Reversible Drum Mixer
Drum Capacity	400 Ltrs.	600 Ltrs.	800 Ltrs.
Output Capacity	8-10 Cum / Hr.	10 - 12 Cum / Hr.	12 - 15 Cum / Hr.
Prime Mover	10 HP	12.5 HP	15 HP
No. of Bins (Inline)	03 Bins - Hydraulic operated with heavy duty power pack		
Storage capacity	0.4 Cum	0.5 Cum	0.75 Cum
Material Weighing	Digital Load Cell based weighing in each bin		
Control Panel	Electrical Device Separate control panel		
Mixing & discharge	Forward rotation for mixing of concrete & Reverse rotation discharges the mixed concrete		
Tyres and Jack	04 nos. of pneumatic tyres and 4 nos. of Pin type jack		
Suggested DG Set	25 KVA	25 KVA	30 KVA



**SOME PHOTOS OF
DISPATCHES OF PLANT**



**SOME PHOTOS OF ERECTION
OF PLANT**



LAL'S
ASPHALT & CONCRETE EQUIPMENT

LAL'S EXPORTERS (INDIA) PVT LTD

CIN - U51390BR2016PTC032154

GSTIN - 10AADCL1199F1ZV

Registered Office:

LAL'S

HOUSE NO. 1, ROAD NO. 07

NORTH JAI PRAKASH NAGAR, PO - ASHIANA

PATNA, BIHAR - 800 025, INDIA

Factory :

AHMEDABAD, GUJARAT, INDIA

Branches :

HARIDWAR, GUWAHATI, JABALPUR, NAGPUR

info@lalsexporters.com

lalsexporters@gmail.com

www.lalsexporters.com

www.lalsequipment.com



+91 87575 95777

+91 87570 14777

+91 98012 85069

***Bigger capacity plants are also available on specific requirement.
For detailed technical specifications, please ask for Techno Commercial Offer.*



LAL'S
ASPHALT & CONCRETE EQUIPMENT

